

# PORTABLE FIRE EXTINGUISHER

## Capacity : 2.2 kg , 4.5 kg, 6 kg, 22.5 kg

DATA SHEET

‘**BENZ**’ brand carbon dioxide (CO<sub>2</sub>) fire extinguishers provide trusted fire protection without contamination risk, A powerful concentration of carbon dioxide gas is delivered onto fires involving flammable liquids and electrical hazards. It not only smothers fires quickly and cleanly but also is non-toxic and harmless to delicate mechanism and materials. Therefore, it is ideally suited for use in laboratories, paint spray booths, switch-gear transformers, diesel locomotives, aircraft, ships and for protecting all kinds of process using oils, spirits, solvents, wax and other highly flammable materials.



### FEATURES

- Seize and Squeeze operation and controllable discharge
- Fire ratings 30% higher than the normal (at least)
- Non-conductive anti-static horns
- Corrosion-resistant cylinder
- Stainless steel levers, chrome plated valves to gain long service life
- **Tested to BSEN3:1996**

### SPECIFICATION

Model No	CDE-5lbs	CDE-10lbs	CDE-10lbs	CDE-15lbs	CDE-15lbs	CDE-50lbs
Nominal capacity (Kg)	2.2	4.5	4.5	6.8	6.8	22.5
Rating	34B	70B	70B	100B	100B	
Discharge Time (sec)	8	16	16	20	20	80
Range (M)	4.5	4.5	4.5	4.5	4.5	4.5
Working Pressure (MPa)	5.6	5.6	5.6	5.6	5.6	5.6
Test Pressure (MPa)	25	25	25	25	25	25
Overall Height (mm)	450	570	570	710	710	1500
Overall diameter (mm)	130	160	160	160	160	200
Full Weight (kg)	7.5	15.5	12.5	20.5	17.5	97
Cylinder Thickness(mm)	4	4	4	4	4	4
Shell Material	Steel	Steel	Alloy steel	Steel	Alloy steel	Steel

**THONGCHARONGLOHAPAN CO., LTD.**



46/2 Soi Chankin, Thoetthai Rd., Bangko, Jomthong, Bangkok, 10150

Tel.02-4766037, 02-4767288 Fax 02-476682 Email: tclfire2007@gmail.com